

for ALE250 Automatic-Feed Soldering Iron and ALE Automatic-Feed Control Unit.



ALES Stand works exclusively with **ALE250 Automatic-Feed Soldering Iron** and **ALE Automatic-Feed Control Unit**.

JBC Intelligent Heat Management automatically detect the tool in the stand and reduces the tip temperature below the solder melting point. Hibernation cuts off power supply preventing oxidation. As a result, tip life lasts up to 5 times longer.

The stand includes **Tip Cleaner** with Brass Wool, as well as, splashguard and antispash membrane to keep the work area clean and free of solder particles. **Quick Cartridge Exchanger** enables a safe, easy and quick cartridge exchange which, combined with **Cartridge Holder**, allows you to store up to four cartridges.

Tool Holder position is easily adjustable to suit your needs and **Cable Collector** is designed for perfect movement adaptation and to keep cables away from the working area.

**Don't believe us...
TRY IT!**



REFERENCE

ALE-SA

SPECIFICATIONS

ESD safe Meet ANSI/ESD S20.20-2021

WEIGHT AND DIMENSIONS

Stand 195 x 93 x 300 mm / 1.48 kg.
7.68 x 3.66 x 11.81 in / 3.25 lb.

Package 342 x 155 x 120 mm / 1.95 kg.
13.46 x 6.10 x 4.72 in / 4.29 lb.

CONNECTABLES

Modular System



ALU

Automatic-Feed Soldering Control Unit

Compatible tools



ALE250-A

Automatic-Feed Soldering Iron